

DATA SHEET

Product Name Non-magnetic Thick Film Chip Resistors

Part Name NM Series

Uniroyal Electronics Global Co., Ltd.

88 Longteng Road, Economic & Technical Development Zone, Kunshan, Jiangsu, China

Tel +86 512 5763 1411 / 22 /33

Email marketing@uni-royal.cn

Manufacture Plant Uniroyal Electronics Industry (kunshan) co., ltd.
Uniroyal Electronics Industry Co., Ltd.
Uniroyal Electronics Global Co.,Ltd Shenzhen Branch
Aeon Technology Corporation
Uniroyal Electronics Global Co.,Ltd Xiamen Branch
Kunshan Foss Electronic material Co., Ltd.

Brands *RoyalOhm* *UniOhm*



1. Scope

- 1.1 This specification for approve relates to the Non-magnetic Thick Film Chip Resistors manufactured by UNI-ROYAL.
- 1.2 Non-magnetic
- 1.3 Suitable for reflow & wave soldering
- 1.4 Application Mobile phone , PDA,Setbox, Meter

2. Part No. System

Part No. includes 14 codes shown as below:

- 2.1 1st~4th codes: Part name. E.g.: NM02,NM03,NM05,NM06,NM12
- 2.2 5th~6th codes: Power rating.

E.g.: W=Normal Size "1~G" = "1~16"

Wattage	1/32	3/4	1/2	1/3	1/4	1/8	1/10	1/16	1/20	1
Normal Size	WH	07	W2	W3	W4	W8	WA	WG	WM	1W

If power rating is lower or equal than 1 watt, 5th code would be "W" and 6th code would be a number or letter.

E.g.: WA=1/10W W4=1/4W

- 2.3 7th code: Tolerance. E.g.: D=±0.5% F=±1% G=±2% J=±5% K= ±10%

- 2.4 8th~11th codes: Resistance Value.

2.4.1 If value belongs to standard value of ≥5% series, 8th code would be zero, 9th~10th codes are significant figures of the resistance and 11th code is the power of ten.

2.4.2 If value belongs to standard value of ≤2% series, 8th~10th codes are significant figures of the resistance, and 11th code is the power of ten.

- 2.4.3 11th codes listed as following:

0=10⁰ 1=10¹ 2=10² 3=10³ 4=10⁴ 5=10⁵ 6=10⁶ J=10⁻¹ K=10⁻² L=10⁻³ M=10⁻⁴

- 2.5 12th~14th codes.

- 2.5.1 12th code: Packaging Type. E.g.: C=Bulk T=Tape/Reel

- 2.5.2 13th code: Standard Packing Quantity.

4=4000pcs 5=5000pcs C=10000pcs D=20000pcs E=15000pcs


Chip Product: BD=B/B-20000pcs TC=T/R-10000pcs

- 2.5.3 14th code: Special features.

E = Environmental Protection, Lead Free, or Standard type.


3. Ordering Procedure

(Example: NM05 1/8W ±5% 10KΩ T/R-5000)




4. Marking

(1) $\pm 1.0\%$ Tolerance: Below 10Ω show as following, read alphabet "R" as decimal point.
Example:




2R20 \rightarrow 2.2 Ω

(2) $\pm 1.0\%$ Tolerance: The first two digits are significant figures of resistance and the third denotes number of zeros following.
Example:



3302 \rightarrow 33K Ω

5. Dimension



Type	Dimension(mm)				
	L	W	H	A	B
NM02(0402)	1.00 \pm 0.10	0.50 \pm 0.05	0.35 \pm 0.05	0.20 \pm 0.10	0.25 \pm 0.10
NM03(0603)	1.60 \pm 0.10	0.80 \pm 0.10	0.45 \pm 0.10	0.30 \pm 0.20	0.30 \pm 0.20
NM05(0805)	2.00 \pm 0.15	1.25 \pm 0.15/-0.10	0.55 \pm 0.10	0.40 \pm 0.20	0.40 \pm 0.20
NM06(1206)	3.10 \pm 0.15	1.55 \pm 0.15/-0.10	0.55 \pm 0.10	0.45 \pm 0.20	0.45 \pm 0.20
NM12(2512)	6.35 \pm 0.10	3.20 \pm 0.20	0.55 \pm 0.10	0.60 \pm 0.25	0.50 \pm 0.20


6. Resistance Range

Type	Power Rating at 70°C	Resistance Range	
		1.0%	5.0%
NM02	1/16W	1 Ω -10M Ω	1 Ω -10M Ω
NM03	1/10W	1 Ω -10M Ω	1 Ω -10M Ω
NM05	1/8W	1 Ω -10M Ω	1 Ω -10M Ω
NM06	1/4W	1 Ω -10M Ω	1 Ω -10M Ω
NM12	1W	1 Ω -10M Ω	1 Ω -10M Ω

7. Ratings

Type	Max. Working Voltage	Max. Overload Voltage	Dielectric withstanding Voltage	Resistance Value of Jumper	Rated Current of Jumper	Max. Overload Current of Jumper	Operating Temperature
NM02	50V	100V	100V	<50m Ω	1A	2A	-55°C~155°C
NM03	75V	150V	300V	<50m Ω	1A	2A	-55°C~155°C
NM05	150V	300V	500V	<50m Ω	2A	5A	-55°C~155°C
NM06	200V	400V	500V	<50m Ω	2A	10A	-55°C~155°C
NM12	200V	500V	500V	<50m Ω	2A	10A	-55°C~155°C

8. Recommend the size of welding plate




Type	Dimension(mm)			
	A	B	C	D
NM02	0.50±0.05	0.45±0.05	0.5±0.05	1.4±0.05
NM03	0.8±0.05	0.65±0.05	0.8±0.05	2.1±0.05
NM05	1.0±0.1	1.0±0.1	1.3±0.1	3.0±0.1
NM06	2.0±0.1	1.1±0.1	1.6±0.1	4.2±0.1
NM12	4.9±0.1	1.6±0.1	3.3±0.1	8.1±0.1

9. Derating Curve

Resistors shall have a power rating based on continuous load operation at an ambient temperature from -55°C to 70°C. For temperature in excess of 70°C, the load shall be derated as shown in figure 1

Figure 1



Voltage rating:

Resistors shall have a rated direct-current (DC) continuous working

voltage or an approximate sine-wave root-mean-square (RMS) alternating-current (AC) continuous working voltage at commercial-line frequency and waveform corresponding to the power rating, as determined from the following formula:

$$RCWV = \sqrt{P \times R}$$


Where: RCWV commercial-line frequency and waveform (Volt.)

P = power rating (WATT.) R = nominal resistance (OHM)


In no case shall the rated DC or RMS AC continuous working voltage be greater than the applicable maximum value.

The overload voltage is 2.5 times RCWV or Max. Overload voltage whichever is less

10. Structure




11. Performance Specification

Characteristic	Limits		Test Method (GB/T5729&JIS-C-5201&IEC60115)
Temperature Coefficient	$1\Omega \leq R \leq 10\Omega : \leq \pm 400 \text{PPM}/^\circ\text{C}$ $10\Omega < R \leq 100\Omega : \leq \pm 200 \text{PPM}/^\circ\text{C}$ $R > 100\Omega : \leq \pm 100 \text{PPM}/^\circ\text{C}$		4.8 Natural resistance changes per temp. Degree centigrade $\frac{R_2 - R_1}{R_1(t_2 - t_1)} \times 10^6 \text{ (PPM}/^\circ\text{C)}$ $\frac{R_3 - R_1}{R_1(t_3 - t_1)} \times 10^6 \text{ (PPM}/^\circ\text{C)}$ R ₁ : Resistance Value at room temperature (t ₁) ; R ₂ : Resistance Value at upper limit temperature ± 2°C (t ₂) R ₃ : Resistance Value at lower limit temperature ± 3°C (t ₃) Test pattern : Room temperature : (t ₁) Upper limit temperature : (t ₂) Lower limit temperature : (t ₃)
Short-time overload	±1%	±(1.0%+0.1Ω) MAX	4.13 Permanent resistance change after the application of 2.5 times RCWV for 5 seconds.
	±5%	±(2.0%+0.1Ω) MAX	
Dielectric withstanding voltage	No evidence of flashover mechanical damage, arcing or insulation breaks down.		4.7 Resistors shall be clamped in the trough of a 90°C metallic v-block and shall be tested at ac potential respectively specified in the given list of each product type for 60-70 seconds.
Solderability	95% coverage Min.		Wave solder: Test temperature of solder: 245°C±3°C dipping time in solder: 2-3 seconds.
	Go up tin rate bigger than half of end pole		Reflow: 
Terminal bending	±(1.0%+0.05Ω) Max		4.33 Twist of test board: Y/X = 3/90 mm for 60Seconds
Rapid change of temperature	±1%	±(1.0%+0.1Ω)Max	4.19 30 min at lower limit temperature and 30 min at upper limit temperature , 5 cycles.
	±5%	±(3.0%+0.1 Ω) Max	
Insulation resistance	1,000 MΩ or more		4.6 The measuring voltage shall be ,measured with a direct voltage of (100±15)V or a voltage equal to the dielectric withstanding voltage., and apply for 1min.
Humidity (steady state)	±1%	±(0.5%+0.1Ω) Max.	4.24 Temporary resistance change after 240 hours exposure in a humidity test chamber controlled at 40±2°C and 90-95% relative humidity,
	±5%	±(3.0%+0.1 Ω) Max	
Load life in humidity	±(1.0%+0.1Ω)MAX.		7.9 Resistance change after 1,000 hours (1.5 hours "ON",0.5 hour "OFF") at RCWV in a humidity chamber controlled at 40°C±2°C and 90 to 95% relative humidity.
Load life	±1%	±(1.0%+0.1Ω)Max	4.25.1 Permanent resistance change after 1,000 hours operating at RCWV with duty cycle 1.5 hours "ON", 0.5 hour "OFF" at 70°C ±2°C ambient.
	±5%	±(3.0%+0.1 Ω) Max	
Low Temperature Storage	±1%	±(1.0%+0.1Ω)Max	4.23.4 Lower limit temperature , for 2H.
	±5%	±(3.0%+0.1 Ω) Max	


High Temperature Exposure	±1%	±(1.0%+0.1Ω)Max	4.23.2 Upper limit temperature , for 16H.
	±5%	±(3.0%+0.1 Ω) Max	
Leaching	No visible damage		J-STD-002 Test D Samples completely immersed for 30 sec in solder bath at 260°C

12. Packing of Surface Mount Resistors

12.1 Dimension of Paper Taping :(Unit: mm)




Type	A ±0.1	B ±0.1	C ±0.05	+0.1 ΦD -0	E ±0.1	F ±0.05	G ±0.1	W ±0.2	T ±0.05
NM02	0.65	1.2	2.0	1.5	1.75	3.5	4.0	8.0	0.42




TYPE	A ±0.2	B ±0.2	C ±0.05	+0.1 ΦD -0	E ±0.1	F ±0.05	G ±0.1	W ±0.2	T ±0.1
NM03	1.10	1.90	2.0	1.5	1.75	3.5	4.0	8.0	0.67
NM05	1.65	2.40	2.0	1.5	1.75	3.5	4.0	8.0	0.81
NM06	2.00	3.60	2.0	1.5	1.75	3.5	4.0	8.0	0.81

12.2 Dimension of Embossed Taping (Unit: mm)



Type	A ±0.2	B ±0.2	C ±0.05	+ 0.1 φD - 0	+0.25 φD1 - 0	E ±0.1	F ±0.05	G ±0.1	W ±0.2	T ±0.1
NM12	3.50	6.70	2.00	1.50	1.50	1.75	5.50	4.00	12.00	1.00

12.3 Dimension of Reel : (Unit: mm)



Type	Taping	Qty/Reel	A±0.5	B±0.5	C±0.5	D±1	M±2	W±1
NM02	Paper	10,000pcs	2.0	13.0	21.0	60.0	178	10
NM03	Paper	5,000pcs	2.0	13.0	21.0	60.0	178	10
NM05	Paper	5,000pcs	2.0	13.0	21.0	60.0	178	10
NM06	Paper	5,000pcs	2.0	13.0	21.0	60.0	178	10
NM12	Embossed	4,000pcs	2.0	13.0	21.0	60.0	178.0	13.8

13. Note

13.1 UNI-ROYAL recommend the storage condition temperature: 15°C~35°C, humidity :25%~75% .

(Put condition for individual product)

Even under UNI-ROYAL recommended storage condition, solderability of products over 1 year old (Put condition for each product) may be degraded.

13.2 Store / transport cartons in the correct direction, which is indicated on a carton as a symbol.

Otherwise bent leads may occur due to excessive stress applied when dropping of a carton.

13.3 Product performance and soldered connections may deteriorate if the products are stored in the following places:

- a. Storage in high Electrostatic
- b. Storage in direct sunshine 、rain and snow or condensation
- c. Where the products are exposed to sea winds or corrosive gases, including Cl₂, H₂S₃ NH₃, SO₂, NO₂.

14. Record

Version	Description of amendment	Page	Date	Amended by	Checked by
1	First issue of this specification	1~7	Mar.20, 2018	Chen Haiyan	Chen Nana

Uniroyal Electronics Global Co., Ltd. , all rights reserved. Spec. herein would be changed at any time without prior notice.