



Cooper Plated Wire Type (CP)



| Part No. | Type | Power Rating at 70°C | Dimension (mm) | | | | Max. Working Voltage | Max. Overload Voltage | Resistance Range |
|----------|---------|----------------------|----------------|--------|--------|-------|----------------------|-----------------------|------------------|
| | | | D Max. | L Max. | d±0.02 | H±3 | | | |
| CP00W4 | CP-25 | 1/4W | 2.5 | 6.8 | 0.5 | 28/38 | 250V | 500V | 1Ω ~ 10MΩ |
| CP00S3 | CP-33-S | 1/3W | 2.5 | 6.8 | 0.5 | 28/38 | 300V | 600V | 1Ω ~ 10MΩ |
| CP00W3 | CP-33 | 1/3W | 3 | 9 | 0.5 | 28 | 300V | 600V | 1Ω ~ 10MΩ |
| CP00S2 | CP-50-S | 1/2W | 3 | 9 | 0.5 | 28 | 350V | 700V | 1Ω ~ 10MΩ |

Cutting Type (CO)



| Part No. | Type | Power Rating at 70°C | Dimension (mm) | | Resistance Range |
|-------------|---------|----------------------|---|---|------------------|
| | | | D | L | |
| CO...W8 | CO-12 | 1/8W | 1.6 ^{+0.10} / _{-0.00} | 3.2 ±0.1 | 1Ω ~ 10MΩ |
| CO...W4 | CO-25 | 1/4W | 2.1 ^{+0.09} / _{-0.00} | 5.6 ^{+0.10} / _{-0.20} | 1Ω ~ 10MΩ |
| CO...W4...A | CO-25-A | 1/4W | 2.1 ^{+0.09} / _{-0.00} | 5.9 ^{+0.10} / _{-0.15} | 1Ω ~ 10MΩ |
| CO...W4...B | CO-25-B | 1/4W | 2.1 ^{+0.09} / _{-0.01} | 6.4 ^{+0.10} / _{-0.15} | 1Ω ~ 10MΩ |

• Cutting type resistors are produced without lead-wire and without coating

• Cap plated option: 1. Tin-plated 2. Nickel-Plated

Ordering Procedure (Example: CP 1/4W 5% H=38mm 10Ω T/B-5000)

